

TransCam L200



A tractor capable of transforming into a Robot



Introducing TransCam L200

**Hybrid power & Battery
operating CCTV Robot
200meters Cable drum
standard package**

TransCam L200

- starting from \geq DN200
- HD camera; 1080P
- motorized camera elevator
- touch screen control tablet
- wheel sets DN200-DN1000

Rugged and durable & Submersible crawler:

The TransCam L200 package includes everything you need as a professional pipe inspection. The simple to use handheld controller with integrated viewing screen includes everything you need to operate your TransCam L200 crawler.

Package includes:

Motorized Lift
PTZ Camera Head
Handheld Controller (Sam Sung Tablet) with voice record option
Cable reel with travel measurement
Inclination sensor
Laser profiler
Big & Small wheels

Unparalleled Performance:

TransCam L200 is the ultimate choice for pipeline inspection, offering unmatched accuracy, versatility, and reliability. Trust in its state-of-the-art technology to safeguard the integrity and performance of your critical needs. .



TransCam L200



A tractor capable of transforming into a Robot



Tractor



Camera



Cable drum



Control pad

Deployment range	from DN200 upwards
Steerable	yes
Drive	6-wheel driven
Inclination sensor	yes
Temperature sensor	yes
Pressure sensor	yes
Overturn protection	yes
Back-eye camera resolution	full HD; 2.1 Megapixels; 1920x1080P
Rear illumination	2 LED
Protection class	IP68, up to 10m water depth
Ambient temperature range	-10~55°C
Wheel sets	4inch, 5inch, 6inch
Dimension	L571xW226xH426mm (6-inch wheel set, full elevator)
Weight	18kg (6-inch wheel set)
Pan & Tilt	360° endless rotation, 150° panning range
Camera resolution	full HD; 2.1 Megapixels; 1920x1080P; PAL
Illumination	4 LED
Auxiliary light	12 LED
Elevator	motorized
Function	defog
Sensitive to light	> 1Lux
Drive	motor-driven
Cable length	200m
Cable tension	250kg
Winding aid	yes
Meter counter	±1% accuracy, min. scale: 1cm
Power	Battery, 10h; power cord (optional)
Battery	lithium iron phosphate battery, 48v/15ah
Communication	Wi-Fi connection to control pad
Protection class	IP65
Dimension & weight	710x390x480mm, 41kg
OS	Android
Display	10.1 inch
Storage	64G
Battery	8h
Size & weight	102x153x63mm, 280g
Communication	Bluetooth 6m
Display information	date, time, tractor position angle, inclination, distance, inspection video, text input, overturn alert and tractor control

Product appearance and specifications are subject to change without notice.